

ARGO Torque Specifications

*Where Avengers differ from other models

Transmission

Side Cover Bolts.....	216 IN. LBS.	24.3Nm
Differential Bolts.....	35 FT. LBS.	47.5Nm
*Shifter Plate Bolts (Avenger).....	75 IN. LBS	8.5Nm

Intake & Exhaust

Kawasaki Exhaust Manifold to Engine.....	204 IN. LBS.	23.2Nm
Kawasaki Muffler to Engine.....	204 IN. LBS.	23.2Nm
Briggs Muffler to Engine.....	204 IN. LBS.	23.2Nm
Briggs Exhaust Man. to Engine.....	204 IN. LBS.	23.2Nm
Kohler Exhaust Man. to Engine (Avenger).....	204 IN. LBS	23.2Nm

Clutch System

Driver Clutch Nut on Clutch.....	100 FT. LBS.	135.6Nm
Driver Clutch Bolt to Briggs Engine.....	50 FT. LBS.	67.8Nm
*Driver Clutch Bolt to Kohler Engine (Avenger).....	40 FT. LBS	54.3Nm
Driver Clutch Bolt to Kaw. Engine	50 FT. LBS.	67.8Nm
Driven Clutch Bolt to Input Shaft.....	15 FT. LBS.	20.3Nm
Spring Cover Cap Screws.....	85IN. LBS.	9.6Nm

Powerpak Assembly

Engine to Powerpak Frame (Kaw).....	30 FT. LBS.	40.7Nm
Engine to Powerpak Frame (Briggs).....	24 FT. LBS.	32.6Nm
*Engine to Powerpak Frame (Kohler).....	35 FT. LBS	47.5Nm
Transmission to Powerpak Frame.....	75 FT. LBS.	101.7Nm
Brake Cooling Air Duct to Frame.....	35 in.lbs.	4.0Nm
Master Cylinder Mounting Bolts.....	96 IN. LBS.	10.7Nm
Belt Guard to Transmission.....	30 FT. LBS.	40.7Nm
Brake Bracket Mounting Bolts.....	240 IN. LBS.	27.1Nm
Power Pack Bolts to Main Vehicle Frame.....	80 FT. LBS	108.4Nm

Fuel System and Seat Assembly

Handrail Assembly to Upperbody	Hand Tight Approx...	48 IN. LBS	5.4Nm
Backpad to Handrail Assembly.....		72 IN.LBS	8.1Nm
Angle Bracket to Seat Assembly.....		72 IN.LBS	8.1Nm
Seat Frame Assembly to Frame.....		72 IN.LBS	8.1Nm
Seat Frame Assembly to Body.....		Snug By Hand	

Electrical System

Battery Retaining Bracket.....		Snug By Hand	
--------------------------------	--	--------------	--